





System DFF 300 UTS

Highly elastic rail fastening for metro – the optimum single support point for slab track

Vossloh fastening systems

Based on our experience we are setting standards of the future.



Urban Transport – Always smooth with stop and go

Frequent starting and stoppings at many stops within the shortest time characterize urban transport. In this case, highly elastic components provide for comfortable travelling at high operating safety and reduced noise – at axle loads of up to 18 t (Metro) / 13 t (Tram).

Direct fastening on slab track

Slab track systems must meet special requirements to deflect forces generated by a rolling train into the ground in a smoothly and material-saving way: The highly elastic components of the rail fastening systems must take over the original elasticity of the ballasted track.

For system DFF 300 UTS, a highly elastic elastomer-intermediate plate made of *cellentic* is used in order to achieve that result. In case of single support points, the system's base plates take over the function of concrete sleepers and their shoulders: they keep

the rail in the track and transfer dynamic forces in the substructure.

System DFF 300 UTS – Flexible, resource-saving application in the slab track

With the DFF 300 UTS system, Vossloh Fastening Systems established a rail fastening system as single support point on a slab track that has been developed on the basis of the approved advantages of the rail fastening system 300 and with this, it has been adapted to the special requirements of urban transport.

Required material quantities are optimized due to the geometry of the plastic base plate.

The high portion of durable plastics ensures corrosion protection and electrical insulation. Compared to steel this light-weight material also provides logistic advantages and an easier handling during installation.



Vossloh protect:

The new coating for tension clamps, sleeper screws and T-head bolts (incl. nuts ans wahsers) – for a consistently and high coating quality.

Advantages

- Conventional barrier protection **plus** cathodic corrosion protection, preventing the base material from corroding in the event of damages, e.g. caused by flying ballast.
- Withstands extreme conditions such as high temperature fluctuations, high humidity and industrial climate (acid rains).

vcellentic

cellentic is an elastomer made of EPDM that ensures high stability against many types of chemical attacks. The advantage: the material provides excellent resistance to temperature, aging, and weather conditions as well as it is very stable under permanent load. *cellentic* components optimize the elasticity for a reduction of vibrations and the protection of track.

System DFF 300 UTS Elastic, Safe, Resilient, Elexible,

The W-shape of the Skl 21 provides safety

For meeting the required *rail creep resistance* two highly elastic, independently acting spring arms steadily hold the rail down; the middle bend acts as an additional *tilting protection*. With its high fatigue strength, it resists the dynamic vertical movements that are caused when the vehicle rolls over the rail. The system is *maintenance-free*: Due to the permanently acting tension, Skl and screw cannot loosen, the middle bend prevents the spring arms from plastic deformation.

A steel plate ensures an optimum distribution of load

A steel plate provides for *load distribution* from the rail foot to the elastic intermediate plate and offers additional *tilting protection* through its large surface. A plastic rail pad insulates the rail electrically.

Adjustable height

Using height adjustment plates, the *height of the system can be adjusted within 30 mm*. With the optimized height adjustment plates *NG* the *cellentic* intermediate plate rests completely on the bearing face.



Angled guide plates keep the rail in the track

The angled guide plates lead the forces introduced into the rail by train in the base plate first and then into the concrete. In this way, the screw-dowel combinations are not loaded by shearing and bending forces. The design of the angled guide plates additionally supports the *tilting protection*. Different widths can *adjust the gauge*.

Highly elastic intermediate plate for low vibration

The elasticity of the special *cellentic* material ensures stable rail deflection; *Vibrations and structure-borne noise are minimised*. Their reinforced edge area also contributes to the *tilting protection*.

Securely clamped with the screw-dowel combination NG

The high-quality dowels made of hightech material are extremely strong and efficient: Lateral forces are reduced, this leads to *a decrease in the load on the slab track.*

Base plate

0

Easy handling for installation and rail maintenance

- Flexibly applicable as single support point: no special shoulders (e.g. for concrete sleepers) required.
- Installation is possible both with bottom up (by bottom casting of base plate) and top-down method.
- For welding of the rail, no fastening elements have to be removed from the support point.
- All components can be replaced.

Safety. Comfort. Track protection.

Travel comfort through optimum rail deflection

The railway track must be elastic to compensate forces caused by running trains. Because ballast is not used for slab tracks, the highly elastic *cellentic* components of the rail fastening system are designed to undertake this job. The DFF 300 UTS system with *cellentic* intermediate plate allows rail deflection and can optimally distribute occurring vertical forces. The result: Protection of track. Its elasticity is adapted to the traffic load to achieve optimum rail deflection: load distribution is at the maximum without overloading the rail. Furthermore, the *cellentic* component damps the vibrations caused by the unevenness of the track and wheels; structure-borne track vibration is minimized. The result: travel comfort, safety through smooth running, as well as increased lifetime of track components and vehicles.

Creep resistance and rail tilting protection

To allow optimum deflection for the rail, its fastening must respond in an elastic way. Therefore, the Skl 21 has a long spring deflection: When force is applied by a train, its spring arms remain in contact with the rail foot in each situation. For this purpose, the rail is continuously clamped in a force-fitted way by the two spring arms with a spring deflection of approx. 14.5 mm and a toe load of approx. 10 kN. With this, also a high creep resistance is achieved: When the trains accelerate/decelerate, the rails remain in position; dangerous fracture gaps due to broken rails are avoided. Simultaneously, a small gap between the middle bend and the rail foot of the rail has exactly the play required for operation. If the rail tilts excessively, e.g. in narrow curves, high forces are applied to the tension clamp. The Skl 21 is able to resist them: Rail movements are limited by the middle bend after the gap has been overcome, and the spring arms are not overstretched.



Simplified demonstration: one axle of a two axle bogie

Load-deflection-curve



Rail fastening system DFF 300 UTS with tension clamp Skl 21		
Typical field of application	Urban transport/Transit; single support point on slab track	
Axle load	≤ 18 t	
Speed	≤ 140 km/h	
Curve radius	≥ 80 m	
Height adjustment	+ 30 mm	
Gauge adjustment	± 10 mm	
Vertical fatigue strength of Skl 21	2.5 mm	
Static stiffness of <i>cellentic</i> intermediate plate	≥ 16 kN/mm	EN 13146-9: 2011
Relation of dyn./stat. stiffness of cellentic intermediate plate	1.1	EN 13146-9: 2011
Toe load of Skl 21 (nominal)	10 kN	EN 13146-7: 2012
Electrical resistance	\geq 10 k Ω	EN 13146-5: 2003
Rail creep resistance	\geq 9 kN	EN 13146-1: 2012
Corrosion protection category (Skl, Ss)	C5-L (1440 h stainless)	ISO 12944
System audit/homologation		EN 13481-5: 2012

Remark: Contents, figures and technical data in this brochure display the performance of the fastening system, however, they always depend on external conditions. Please contact us to enable us to develop a solution for you that will be customized to your requirements. The information presented corresponds to the technical state at the time of printing; in the meantime, continuous research and development programmes at Vossloh could have caused adaptations of the product.



Vossloh Fastening Systems GmbH Vosslohstraße 4 D-58791 Werdohl
 Phone
 +49 (0) 23 92 52-0

 Fax
 +49 (0) 23 92 52-448

 E-Mail
 info.corecomponents@vossloh.com

The trademarks Vossloh, **vossloh**, **v**, *cellentic* and *amalentic* are registered trademarks, which are internationally protected in many countries. These trademarks may only be used with prior consent by Vossloh AG. This publication may also contain trademarks of third parties. The use of those trademarks is subject to the terms of use of the respective owner.